



**Energy Storage (ES) Supported  
Photo-Voltaic (PV) Power Conditioning,  
including  
Ancillary Services Provision and Isolated  
Grid Support**

- **Commercial to Utility Scale PV Power Conditioning *today*:**
  - ✓ **PowerGate® Plus three-phase PV Inverters;**
  - ✓ **PV Plant Installations; and**
  - ✓ **PV View™ Plus, Remote Monitoring and Energy Management Systems.**
  
- **Utility Scale PV + ES Power Conditioning *tomorrow*:**
  - ✓ **PV + ES Inverter Power Train;**
  - ✓ **Ancillary Service Provision; and**
  - ✓ **Island Grid / MicroGrid Operation Capability.**
  
- **SatCon PV + ES Electrical Power Equipment Packages:**
  - ✓ **PV + ES Power Converter System; and**
  - ✓ **Project Management, Engineering, Manufacturing, Installation, Commissioning and After-Market Services.**

## ➤ PowerGate® Plus Photovoltaic Inverters (Gen II):



- First turn of the product line since its introduction, since 2004;
- Designed for Higher Efficiency, Shorter Lead Times, and the Next Level of Durability and Reliability; and
- 100+ MW of PowerGate PV Inverters delivered 2007.

## ➤ PowerGate® Plus Photovoltaic Inverters (Gen II):

Attribute	Highlights
Efficiency	✓ Continued leadership in efficiency.
Ease of Installation	✓ Improved ease of cabling.
Service	✓ Inverter Monitoring with Help Desk.
Technology	✓ State of the Art Digital Controls. ✓ Industrial grade equipment.
Reliability	✓ G90 galvanized steel enclosure. ✓ Printed circuit boards for- 40° C to plus 85° C range.
Economics	✓ Introduction of 250kW, 375kW(UL), 400kW(CE), and 1000kW(UL & CE) ratings. ✓ State of the art, Maximum Power Point Tracking (MPPT) algorithm for improved energy harvesting.

**225kW Ground  
Based Installation**





**1.6MW Building  
Integrated PV  
(BIPV) Plant  
Installation at  
Google's corporate  
headquarters in  
Mountain View, CA  
equipped with  
PowerGate®  
PV Inverters**



## ➤ PV View™ Plus Remote Monitoring System:

- Introduced in Late 2007:
  - ✓ Beta System operating in NJ since June of 2007.

Home Page




Energy Reporting

# Utility Scale PV + ES Power Conditioning *tomorrow*

3.3-35kV, 50/60Hz Feeder

## PV + ES Inverter Power Train




The information of this document is the confidential information of SatCon Power Systems and is not to be reproduced without written permission by SatCon Power Systems



➤ PV + ES Inverter Power Train

MV AC Power OUT



## ➤ PV + ES Inverter Power Train Application Versatility

Aside of PV power conditioning Inverter Units, when combined with energy storage device, can also be applied for:

1. Voltage regulation via dynamic VAR injection/modulation (STATCOM role) including voltage sag compensation;
2. BIPV Customer demand peak shaving/utility load following;
3. Utility Ancillary Services such as:
  - ⇒ Frequency Keeping/Regulation;
  - ⇒ Instantaneous Reserve for frequency recovery after U/F events; and
  - ⇒ High-Inertia Generation to resist developing frequency deviations.

- ✓ **Power Train (PT) Inverter Unit Redundancy/Improved Uptime:**
  - ⇒ Through addition of redundant Inverter Unit(s) in PT.

## ➤ PV + ES Inverter Power Train Ancillary Service Provision

Item No:	Feature Description	ES Required	Impact on Inverter Size/Price
1	<b>Distributed Spinning Reserve (DSR)</b> - WATTs Generation on Demand	Yes, <b>15 - 30 minutes</b>	Inverter kVA Rating = <b>kW (PV)+ kW (DSR)</b>
2	<b>Distributed Frequency Regulation (DFR)</b> - WATTs Gener. and Absor. on Demand	Yes, <b>30-60 minutes</b>	Bi-direct. Inverter kVA Rating = <b>kW (PV) +/- kW (DFR)</b>
3	<b>Utility Load Following (ULF)</b> - Boosting the PV Generation Capacity Value	Yes, <b>2 - 4 hours</b>	Inverter kVA Rating = <b>kW (PV), + Boost Chopper</b>
4	<b>Frequency Stability Support (FSS)</b> - High Inertia Behavior of PV Generator	Yes, <b>30-60 seconds</b>	Inverter 10-sec kVA Rating = <b>kW (PV)+ 10-second kW (FSS)</b>
5	<b>Grid Faults / LV Ride Through (LVRT)</b> - An alternative to Anti-Islanding	Yes, <b>1-10 seconds</b>	<b>No Impact</b> on Inverter Size, Minimum Impact on Inverter Price.
6	<b>Dynamic Voltage Support (DVS)</b> - Capacitive and Inductive VARs Generation	No	Inverter kVA Rating = <b>SR(kW (PV) **2 + kVAR (DVS)**2)</b>

# Summary for Ancillary Services Capable DG

---

## ➤ PV + ES Inverter based and Ancillary Service Capable DG Benefits

1. Value of ancillary services can be significant and can represent *an incremental revenue stream* for DG owners;
2. Low cost communication and monitoring or SCADA facilities would *extend aggregation opportunities* for DG to participate in the ancillary service market;
3. Higher penetration of DG will *increase ISO options regarding T&D grid operation* and development decisions which can lead to:
  - ⇒ *Lower overall operating costs; and*
  - ⇒ *Enhance competition in ISO markets for frequency control and spinning reserve as the demand for these services increase with intermittent renewable generation.*

## ➤ PV + ES Inverter Power Train for An Island Grid / MicroGrid Application

Consider an *application case* of existing PV and Fuel Cell (FC) on-site generation equipment, owned by nearby critical facility, whose original purpose was to:

1. Provide local facility load support through on-site generation; and
2. To sell excess green / clean power to utility grid customers.

**Can the existing grid-connected PV and FC on-site generation be retrofitted with ES to provide for critical facility load support during utility grid outages?**

- ⇒ Without any modifications to the existing grid-connected power electronics and controls?
- ⇒ Without any significant re-adjustments of facility load profile?




The answers are **positive** to all questions!

Existing normally grid connected PV and FC generation can be made to support an islanded distribution portion of the utility grid or critical facility related micro-grid during utility grid outages by retrofitting the island grid with following additional equipment:


- ⇒ **A suitably rated AC-Connected Energy Storage System (ACCESS); and**
- ⇒ **A fast, Sub-cycle / Static Disconnect Switch (SDS).**

# ACCESS and a SDS Enable Support of an Island Grid

**ENERGY STORAGE UNIT  
CONTROLS VOLTAGE AND  
FREQUENCY IN ISLAND MODE**




**STATIC  
DISCONNECT  
SWITCH (SDS)**




480 V, 60 Hz


**1000 kW max** ↔ **NEW ENERGY STORAGE**



**500 kW max** ← **EXISTING FUEL CELL**



**500 kW max** ← **EXISTING PV ARRAY**




**ISLAND GRID**

The information of this document is the confidential information of SatCon Power Systems and is not to be reproduced without written permission by SatCon Power Systems

# ACCESS - Single Stage Power Conversion From DC Energy Storage to AC Bus



**Energy Storage Device Determines DC Voltage**



**Converter Control Determines Current to/from Storage Device**


SatCon Multi-Input, Single-Stage, 2.4 MW, 13.8 kV, custom-engineered and built power converter system (PCS)  
- 4 x 600 kW converters with external transformer (not shown).



# Two-Stage ACCESS- From DC Energy Storage to AC Bus uses Optimum DC Filter Voltage

**DC/DC Chopper  
Determines  
Current to/from  
Storage Device**

**DC/AC Converter  
Control Determines  
DC Filter Voltage**




SatCon Multi-input, 2-stage,  
1.5 MW, 480 VAC PCS  
- 4 x 375 kW converters with internal  
transformers.



## Medium Voltage Sub-cycle Disconnect Switches (MV SDS)

- Sub-cycle voltage sag sense & disconnect times, half-cycle, or 10ms max,
- Solid-state (thyristor valve based) switching, up to 35kV system voltage and 25kA fault isolation rating,
- Static, wear & tear-free, including switching parts,
- Equipped with conventional service isolation and bypass disconnects.

## SatCon MV Sub-cycle Disconnect Switch






## ➤ Energy Storage options by length of required outage support:

- Long term (minutes/hours) storage
  - various battery technologies (cells have defined capacity)
  - flow batteries (storage capacity depends on electrolyte volume)
- Short term (< 1 minute)
  - transitional power for brief grid outages or while fueled generation is started
  - flywheels
  - ultra-capacitor bank

# Flow Battery - Output KVA depends on Power Converter, Stored Energy Depends on Electrolyte Volume



SatCon Power Converter  
System (375 kVA/250 kW)  
+ VRB Flow Battery (2 MWh)  
- PacifiCorp, Castle Valley, Utah

# Diesel Generator with Flywheel Energy Storage Provides No-Break Power for an Island Grid

**Diesel (normally at rest) provides continuous power (through clutch) when needed**

**Low-speed flywheel provides full output for 12 seconds during engine startup**

SatCon flywheel generator with coupled diesel engine regulates voltage/frequency while supplying 2.2 MVA output to an AC Grid

## SatCon Rotary UPS Installation for NIST, CO




# Ultra-Capacitors are a Static Alternative for Transitional Power while Fueled Generation is Started



Capacitor + DC/AC Converter can replace Flywheel Generator



**MAXWELL TECHNOLOGIES  
BMOD0063 P125  
MODULE  
63 F, 125 V  
150 A CONTINUOUS  
SERIES CONNECTION TO 1500 V  
20 YEAR LIFE ACHIEVABLE**




Number of modules for specified power and useable energy depends on working DC voltage range selected

The information of this document is the confidential information of SatCon Power Systems and is not to be reproduced without written permission by SatCon Power Systems



# Simulink Model of Island- Micro-Grid with SDS, Fuel Cell, ACCESS for 2.2 MVA Critical Facility Load




The information of this document is the confidential information of SatCon Power Systems and is not to be reproduced without written permission by SatCon Power Systems



# Simulated 3-Phase Fault on Utility Grid


## 2.2 MVA, 0.8 P.F. Constant Load on Island Grid



The information of this document is the confidential information of SatCon Power Systems and is not to be reproduced without written permission by SatCon Power Systems


# Simulated Single-Phase Fault on Utility Grid

## 2.2 MVA, 0.8 P.F. Constant Load on Island Grid



The information of this document is the confidential information of SatCon Power Systems and is not to be reproduced without written permission by SatCon Power Systems

# Simulated Operation in Island Mode - Load Suddenly Increased (1.1 to 2.2 MVA, 0.8 P.F.)



The information of this document is the confidential information of SatCon Power Systems and is not to be reproduced without written permission by SatCon Power Systems

- **Scope of Equipment Supply (Major Power System Components), to provide for Island- or Micro-Grid island operation in retrofit applications, includes:**
  - 1. Bi-directional Power Conditioning System (B-PCS);**
  - 2. Short-term or Long-term Energy Storage Device (S-ESD or L-ESD);**
  - 3. Medium Voltage Sub-cycle Disconnect Switch (MV SDS).**

- **Scope of Equipment Supply (Major Power System Components) to provide for Private- Micro- Grid Island enable operation in new, "green-field" applications, includes:**
  - 1. Bi-directional Power Converter System (B-PCS) combined with Unidirectional Power Converter System (U-PCS) for Clean-Energy Source (Fuel Cell, PV Array or Wind Turbine) utility grid interface ;**
  - 2. Short-term or Long-term Energy Storage Device (S-ESD or L-ESD);**
  - 3. Low Voltage or Medium Voltage Sub-cycle Disconnect Switch (LV-SDS or MV-SDS).**



- **SatCon – Project Management, Engineering, Manufacturing, Installation, Commissioning and After-Market capabilities provide for:**
  - 1. Island- Micro-Grid Power System *Design Engineering*;**
  - 2. *Project Management* and *Electrical & Controls Equipment Manufacturing*;**
  - 3. Through an ES Partner: *Energy Storage Device Engineering and Manufacturing*;**
  - 5. Through an Electrical Contractor: the performance of *Civil Works and Equipment Installation*;**
  - 6. SatCon and ES Partner: to perform *Power System Commissioning and After-Market Services (Warranty, PM or Extended Warranty contracted Services)*;**
  - 7. SatCon and ES Partner, to perform *Project Performance Reporting*.**

## Summary for Isolated Grid

- Addition of **AC-Connected Energy Storage System (ACCESS)** equipment to an existing alternative energy generation equipment installation increases the DG installation value by:
  - enabling existing generation *to support critical, local facility load during utility outages*; and
  - allowing more *cost-effective energy efficiency management* when the utility grid is available.
- Addition of a fast **Static Disconnect Switch (SDS)** equipment *allows separation from a faulted utility grid* without significant deviation of the micro-grid AC bus voltage, *enables the facility load ride-through/operation continuity*.

**Thank you for your attention.**

**Contact:**

✓ **(905) 639-4692**

✓ **Janos.Rajda@SatCon.com**